

UD-1600KI

Network Keyboard



Features

- 10.1" capacitive touchscreen;
- Detachable design of the touchscreen and joystick;
- Wired and WiFi network connection;
- POE power supply;
- Capable of decoding 2-ch at 1080P decoding; up to 16-division window display;
- Live view on touch panel;
- DVI and HDMI output to monitor;
- Controllable of 8000 devices;
- Access to products including DVR, DVS, NVR, network camera, speed dome, etc.;
- Control of MVC and decoders for video decoding and output on video wall;
- Accessible to U-Center
- Add cameras in batches by importing an Excel file from a USB drive
- PTZ control, setting and calling preset, patrol and pattern;
- Support upgrade and configuration files import/export by USB flash disk;
- Support recording and picture capturing; saving files in USB flash disk or uploading to FTP server;
- Two-level user authority and up to 32 user accounts are configurable: one admin and 31 operators.

Specification

Model	UD-1600KI
Operating System	Android 6.0
TFT LCD Screen	10.1" TFT LCD touchscreen Resolution: 1280 × 800
Joystick	4-axis joystick
Local Decoding	Local live view at 1080P/720P/HD1/BCIF/CIF/QCIF resolution, and up to 16-division window display
Two-way Audio Input	1-ch, 3.5mm connector (2.0Vp-p, >1kΩ)
Audio Output	1-ch, 3.5mm connector (2.0 Vp-p, 600 Ω)
Network Interface	10M/100M/1000M Adaptive Ethernet port
WiFi	Supported
USB Interface	USB 2.0 × 2
Video Interface	HDMI, DVI
Power Supply	12V DC /POE
Consumption	≤15W
Working Temperature	-10°C -- +55°C
Working Humidity	10%--90%
Dimensions (W × D × H)	404 × 180 × 163 mm
Weight	1.7 Kg

