

# UN-DW2725I-ZP

## 2MP Dome Network Camera



- 1/2.8" 2Magapixel progressive scan CMOS
- Support H.265/H.264/MJPEG compression codec
- Max 25/30fps@2M (1920x1080)
- Smart Detection supported
- WDR (120dB), Day/Night (ICR), 3DNR,AWB, AGC, BLC
- 2.7mm ~ 12 mm vary-focal lens
- Max. IR LEDs Length 30m
- Micro SD memory, IP67, PoE
- Manufacturing by ISO14001-2015,ISO9001:2015 Company



### Specification

Model	UN-DW2725I-ZP
Image Sensor	1/2.8" 2Mega pixel progressive scan CMOS
Effective Pixels	1920(H)x1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3s~1/100000s, Slow Shutter
Min. Illumination	0.005Lux/F1.2(Color), 0.001Lux/F1.4(B/W), 0Lux(IR on)
S/N Ratio	More than 50dB
Video Output	1Vp-p composite output (75 Ω/BNC)
Alarm	1 input, 1 output
<b>Camera Features</b>	
Max. IR LEDs Length	30m
Day/Night	Schedule / Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / WDR(120dB)
White Balance	Auto/Sunny/Night/Outdoor/Customized
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Privacy Masking	Up to 4 areas
<b>Lens</b>	
Focal Length	2.8mm~12mm
Max Aperture	F1.4
Focus Control	Auto



Model		UN-BW2625I-ZP
Angle of View		H: 105°~35°, V: 56°~20°
Lens Type		Motorized
Video		
Compression		H.265+/H.265/H.264+/H.264H/MJPEG
Resolution		2M(1920x1080)/720P(1280x720)/D1(640x480)/CIF(320x240)
Frame Rate	Main Stream	1920x1080/1280x720 (1 ~ 25/30fps)
	Sub Stream	640x480/320x240 (1 ~ 25/30fps)
	Third Stream	1920x1080/1280x720/640x480/320x240 (1-25/30fps)
Bit Rate		32Kbps ~ 16Mbps
Audio		
Compression		G.711/ G.722.1/G.726/MP2L2/PCM
Interface		1/1 channel In/Out
Smart Function		
Smart detection	Line crossing	
	Intrusion	
	Object removal	
	Scene Change	
	Face detection	
Motion detect		Yes
Perimeter Protection		Recognition of human and vehicle
Region of Interest		Yes
Network		
Communication Interface		1 RJ45 10M/100M self-adaptive Ethernet port
Network Storage		Support Micro SD/SDHC/SDXC (128G), local storage and NAS (NFS,SMB/CIFS), ANR
Alarm Trigger		Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error, Alarm input, Alarm output
General Function		One-key reset, anti-flicker, three streams, heartbeat, password protection, privacy mask, watermark, IP address filter
Protocols		TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv4/IPv6, Bonjour
API		CGI, ISAPI, PSIA, SDK
Simultaneous Live View		Up to 6 channels
User/Host		Up to 32 users, 3 levels: Administrator, Operator and User
Web Browser		IE, Chrome, Firefox, Safari
Smart Phone		IOS, Android
General		
Operating Conditions		-30 °C to +60 °C (-22 °F to +140 °F), Humidity 95% or less (non-condensing)
Power Supply		12 VDC ± 25%, PoE (802.3at)
Power Consumption and Current		12 VDC, 0.75A, max. 9.5W PoE (802.3af, 37V to 57V), 0.1A to 0.3A, max. 11W
Protection Level		IP67, IK10
Certification		CE/FCC/UL
Material		Metal
Dimensions		Φ153.4×133.1 mm (Φ6.04"× 5.24")
Weight		Camera : Approx. 1287 g (2.84 lb.)

Dimension

